

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date	28. October 2012	Version	4.0
Revision date	04. December 2019		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
Substance / mixture
Catalyst (for silicone filling 011,019,021,029)
mixture
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
Catalyst.
Mixture uses advised against
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Supplier
Name or trade name
AG TermoPasty Grzegorz Gąsowski
Address
Kolejowa 33 E, Sokoły, 18-218
Poland
Identification number (CRN)
200133730
VAT Reg No
9661767714
Phone
862741342
E-mail
biuro@termopasty.pl
Web address
www.termopasty.pl
- Competent person responsible for the safety data sheet**
Name
AG TermoPasty Grzegorz Gąsowski
E-mail
biuro@termopasty.pl
- 1.4. Emergency telephone number**
112 National Health Service (NHS) 111
National poisoning information centre Scotland, NHS 24: 111

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
The mixture is classified as dangerous.

Flam. Liq. 3, H226
Eye Irrit. 2, H319
Acute Tox. 4, H332
STOT SE 3, H335
STOT SE 2, H371

Full text of all classifications and hazard statements is given in the section 16.

Most serious adverse physico-chemical effects

Flammable liquid and vapour.

Most serious adverse effects on human health and the environment

Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause damage to organs.

- 2.2. Label elements**

Hazard pictogram



Signal word

Warning

Hazardous substances

ethyl silicate
Dilaurylian dioktylocyny

Hazard statements

H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date	28. October 2012	Version	4.0
Revision date	04. December 2019		

- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H371 May cause damage to organs.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 Do not breathe vapours.
- P280 Wear eye protection.
- P312 Call a POISON CENTER if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use powder extinguisher/sand/carbon dioxide to extinguish.

2.3. Other hazards

Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note.
Index: 014-005-00-0 CAS: 78-10-4 EC: 201-083-8	ethyl silicate	>25	Flam. Liq. 3, H226 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	1
CAS: 3648-18-8 EC: 222-883-3 Registration number: 01-2119979527-19-XXXX	Dilaurynian dioktylocyn	15	STOT SE 2, H371	

Notes

1 Substance for which exposure limits of Community for working environment exist.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water/shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Provide medical treatment.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date	28. October 2012	Version	4.0
Revision date	04. December 2019		

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause respiratory irritation.

If on skin

Not expected.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date	28. October 2012	Version	4.0
Revision date	04. December 2019		

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Use only non-sparking tools. Wash hands and exposed parts of the body thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

Store in tightly closed containers in a cool, dry place intended for this purpose.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Substance name (component)	Type	Time of exposure	Value	Note	Source
ethyl silicate (CAS: 78-10-4)	OEL	8 hours	44 mg/m ³		Směrnice Komise (EU) 2017/164
	OEL	8 hours	5 ppm		

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
ethyl silicate (CAS: 78-10-4)	WEL	8 hours	87 mg/m ³	The UK Advisory Committee on Toxic Substances has expressed concern that, for the OELs shown in parentheses, health may not be adequately protected because of doubts that the limit was not soundly-based. These OELs were included in the published UK 2002 list and its 2003 supplement, but are omitted from the published 2005 list.	Gestis
	WEL	Short-term	260 mg/m ³	The UK Advisory Committee on Toxic Substances has expressed concern that, for the OELs shown in parentheses, health may not be adequately protected because of doubts that the limit was not soundly-based. These OELs were included in the published UK 2002 list and its 2003 supplement, but are omitted from the published 2005 list.	

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date	28. October 2012	Version	4.0
Revision date	04. December 2019		

United Kingdom of Great Britain and Northern Ireland

Substance name (component)	Type	Time of exposure	Value	Note	Source
ethyl silicate (CAS: 78-10-4)	WEL	8 hours	10 ppm	The UK Advisory Committee on Toxic Substances has expressed concern that, for the OELs shown in parentheses, health may not be adequately protected because of doubts that the limit was not soundly-based. These OELs were included in the published UK 2002 list and its 2003 supplement, but are omitted from the published 2005 list.	Gestis
	WEL	Short-term	30 ppm	The UK Advisory Committee on Toxic Substances has expressed concern that, for the OELs shown in parentheses, health may not be adequately protected because of doubts that the limit was not soundly-based. These OELs were included in the published UK 2002 list and its 2003 supplement, but are omitted from the published 2005 list.	

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Physical state	liquid at 20°C
color	yellow
Odour	characteristic
Odour threshold	data not available
pH	6 (undiluted)
Melting point/freezing point	data not available
Initial boiling point and boiling range	90 °C
Flash point	63 °C
Evaporation rate	data not available
Flammability (solid, gas)	data not available
Upper/lower flammability or explosive limits	
flammability limits	data not available

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date	28. October 2012	Version	4.0
Revision date	04. December 2019		

explosive limits	data not available
Vapour pressure	2 hPa at 20 °C
Vapour density	data not available
Relative density	data not available
Solubility(ies)	
solubility in water	insoluble
solubility in fats	data not available
Partition coefficient: n-octanol/water	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
Viscosity	0.53 cP
Explosive properties	Vapours mixed up with air can be explosive.
Oxidising properties	data not available
9.2. Other information	
Density	0.939 g/cm ³
ignition temperature	data not available

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

No toxicological data is available for the mixture.

Acute toxicity

Harmful if inhaled. May cause damage to organs.

ethyl silicate

Route of exposure	Parameter	Value	Time of exposure	Species	Sex
Oral	LD ₅₀	6.270 mg/kg		Rat	
Dermal	LD ₅₀	5.85 mg/kg		Rabbit	
Inhalation (vapor)	LC ₅₀	5.03 mg/l	4 hour	Rat (Rattus norvegicus)	
Inhalation (vapor)	LC ₅₀	1000 ppm	4 hour	Rat (Rattus norvegicus)	

Skin corrosion/irritation

Based on available data the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date 28. October 2012
Revision date 04. December 2019 Version 4.0

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation. May cause damage to organs.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. Based on available data the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Acute toxicity

Data for the mixture are not available.

ethyl silicate

Parameter	Value	Time of exposure	Species	Environment
EC ₅₀	>844 mg/l	48 hour	Daphnia (Daphnia magna)	
EC ₅₀	>2 mg/l	5 hour	Bacteria (Pseudomonas putida)	

12.2. Persistence and degradability

Not available.

12.3. Bioaccumulative potential

Not available.

12.4. Mobility in soil

Not available.

12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6. Other adverse effects

Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date 28. October 2012
Revision date 04. December 2019 Version 4.0

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

- 14.1. UN number**
UN 1993
- 14.2. UN proper shipping name**
FLAMMABLE LIQUID, N.O.S.
- 14.3. Transport hazard class(es)**
3 Flammable liquids
- 14.4. Packing group**
III - substances presenting low danger
- 14.5. Environmental hazards**
not available
- 14.6. Special precautions for user**
Reference in the Sections 4 to 8.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**
not available

Additional information

Hazard identification No.	30 (Kemler Code)
UN number	1993
Classification code	F1
Safety signs	3



Road transport - ADR

Special provision	274, 601
Limited quantities	5 L
Excepted quantities	E1
Packaging	
Packing instructions	P001, IBC03, LP01, R001
Mixed packing provisions	MP19
Portable tanks and bulk containers	
Guidelines	T4
Special provision	TP1, TP29
ADR tank	
Tank code	LGBF
Vehicles for tank carriage	FL
Transport category	3
Tunnel restriction code	(D/E)
Special provision for packages	V12
operation	S2

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date	28. October 2012	Version	4.0
Revision date	04. December 2019		

Railway transport - RID

Special provision 274, 601

Packaging

Packing instructions P001, IBC03, LP01, R001

Mixed packing provisions MP19

Portable tanks and bulk containers

Guidelines T4

Special provision TP1, TP29

RID Tanks

Tank code LGBF

Transport category 0

Special provision for

packages W 12

Marine transport - IMDG

EmS (emergency plan) F-E, S-E

MFAG 310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended.

15.2. Chemical safety assessment

not available

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H371 May cause damage to organs.

Guidelines for safe handling used in the safety data sheet

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P280 Wear eye protection.

P312 Call a POISON CENTER if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use powder extinguisher/sand/carbon dioxide to extinguish.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by road

BCF Bioconcentration Factor

CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures

DNEL Derived no-effect level

EC Identification code for each substance listed in EINECS

EC₅₀ Concentration of a substance when it is affected 50% of the population

EINECS European Inventory of Existing Commercial Chemical Substances

SAFETY DATA SHEET



according to Regulation (EC) No 1907/2006 (REACH) as amended

Catalyst (for silicone filling 011,019,021,029)

Creation date	28. October 2012	Version	4.0
Revision date	04. December 2019		

EmS	Emergency plan
EU	European Union
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
IC ₅₀	Concentration causing 50% blockade
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
LOAEC	Lowest observed adverse effect concentration
LOAEL	Lowest observed adverse effect level
log Kow	Octanol-water partition coefficient
MARPOL	International Convention for the Prevention of Pollution From Ships
NOAEC	No observed adverse effect concentration
NOAEL	No observed adverse effect level
NOEC	No observed effect concentration
NOEL	No observed effect level
OEL	Occupational Exposure Limits
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted no-effect concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bioaccumulative
Acute Tox.	Acute toxicity
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
STOT SE	Specific target organ toxicity - single exposure

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.