Product Technical Data Sheet

MANUFACTURER: AG Termopasty Grzegorz Gąsowski
ul. Kolejowa 33 E, 18-218 Sokoły, phone 86 274 13 42

Kontakt U

The formulation is a composition of solvents that allows cleaning and degreasing of electrical components and contacts. Kontakt U is an agent that effectively removes residual grease, dirt; old lubricants, oils, silicones, sulphides and oxides dissolved with Kontakt S as well as any soldering residues (including rosin). The formulation protects against corrosion and ensures low contact transition resistance.

Application:

- degreasing of components and contacts,
- cleaning of components and contacts,
- good lubricating properties.

Physicochemical properties of the liquid:

Parameters	UoM	Result
Relative density at 20°C	g/cm^3	0,74
Viscosity	MPa·s	18,6

Packagings:

Volume	Type of packaging	Collective packaging	Item Code
60 ml	aerosol	4 / 20	ART.AGT-011
300 ml	aerosol	4 / 40	ART.AGT-012
400 ml	aerosol with brush	4 / 24	ART.AGT-226
1 L	metal bottle	1	ART.AGT-097

Warehousing:

Store in sealed containers in dry and well ventilated areas away from sources of heat and ignition and direct sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect against electrostatic discharge.

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.