# Product Technical Data Sheet

**MANUFACTURER:** AG Termopasty Grzegorz Gąsowski
ul. Kolejowa 33 E, 18-218 Sokoły, phone 86 274 13 42

# Grease with molybdenum disulfide

The grease reduces friction of metal parts to a minimum. Provides long lasting protection against rinsing and abrasion. It perfectly protects elements of the suspension systems, steering systems, and any moving parts of the chassis.

## Application:

lubrication of all moving parts in mechanical and industrial vehicles operating in a humid environment (e.g. cranes, forklifts, jib cranes, hoists etc.)

## Physicochemical properties:

| Parameters | UoM | Result |
|---|---|---|
| Colour | - | black |
| Release of oil from grease at 100°C within 24 hours | % | 0,2 |
| Drop point | °C | 196 |
| Penetration at 25°C after kneading | mm/10 | 294 |

## Packagings:

| Volume | Type of packaging | Collective packaging | Item Code |
|---|---|---|---|
| 100 ml | aerosol | 4 / 20 | ART.AGT-152 |
| 400 ml | aerosol | 4 / 12 | ART.AGT-174 |

## Warehousing:

Store in a well-ventilated, cool place. Keep away from children. Protect from sunlight and do not expose to temperatures exceeding 50°C. Professional application: keep in original, properly labelled, airtight containers in a cool, dry, well ventilated storage room (in a fireproofed building).

Data contained in this document are consistent with the current state of our knowledge. They describe typical product properties and applications. However, it is up to the user to examine the suitability of this product for specific applications. We deny liability for the obtained results on the grounds that application conditions lie beyond our control.